



PRODUCT OVERVIEW

- The Quantum core switch series provides robust Layer 2 switching and advanced Layer 3 routing features to meet the mission-critical needs of data centre, enterprise and healthcare and education institution networks.
- Quantum Networks switches can be managed through Rudder controllers (cloud-hosted or on-prem), device GUI/CLI and SNMP.
- The core switches support multiple configurations – 16 to 48 ports of 10G/1G. In addition, they support 2 to 6 ports of 100G/40G uplinks.
- The switches support hot-swappable, redundant power supplies and fans; which are essential for fault tolerant environments like Data centre Top-of-Rack, Enterprise Core/Distribution and Cloud service provider network deployments.
- On-device management ports include a dedicated console port, an out-of-band management port and a USB flash drive port for storage.
- Quantum core switches deliver outstanding throughput, resiliency and scalability for organizations with high-performance network requirements.
- Three-year limited liability manufacturer's warranty from day one.

HIGHLIGHTS

- **Simplified network management**
Quantum Core Series Switches support redundant hot-swappable power supplies, fan redundancy, a choice of L2 and L3 multi-pathing designs and application-level performance monitoring and virtualization.
- **Centralized network observability**
Dashboards and reporting logs for diverse network occurrences.
- **Reliable performance**
Provides stability, scalability, and seamless management of varied workloads.
 - The Core switch supports up to 2160 Gbps of wire-speed switching capacity and up to 1607 Mpps of forwarding capacity, allowing it to handle a wide range of workloads.
 - For better network security, the switch supports multiple authentication methods, including 802.1x and MAC authentication. The switch provides identity-driven security and controls via granular Access Control Lists (ACLs).

KEY SPECIFICATION

Communication Ports	Specification					
Model	10G/1G Fiber Downlinks	1G Fiber Downlinks	1G Combo Downlinks	100G/40G Fiber Uplinks	10G/1G Fiber Uplinks	100G/40G Fiber Dedicated stacking ports
QN-CS-4810GF	48	NA	NA	4+2*	NA	2*
QN-CS-2410GF	24	NA	NA	4+2*	NA	2*
QN-CS-1610GF	16	NA	NA	2*	NA	2*
QN-CS-241GF	NA	16	8	NA	4	NA
Management Ports	QN-CS-4810GF	QN-CS-2410GF	QN-CS-1610GF	QN-CS-241GF		
Management (OOB)	1	1	1	1		
Console (RJ45)	1	1	1	1		
Storage (USB Type A)	1	1	1	1		
Capacity	QN-CS-4810GF	QN-CS-2410GF	QN-CS-1610GF	QN-CS-241GF		
Switching capacity	2160 Gbps	1680 Gbps	720 Gbps	128 Gbps		
Forwarding rate	1607 Mpps	1250 Mpps	536 Mpps	95.23 Mpps		
MAC address table	32k, 64k***	32k, 64k***	32k	16k		
Packet buffer size	6MB	6MB	6MB	3MB		
VLANs support	4096	4096	4096	4096		
Maximum jumbo frame size	9,216 bytes	9,216 bytes	9,216 bytes	9,216 bytes		
Link aggregation groups	Max 32	Max 32	Max 32	Max 32		
Link aggregation ports per group	Max 8	Max 8	Max 8	Max 8		
QoS priority queues	8 per port	8 per port	8 per port	8 per port		
Quality of Service						
DiffServ (Differentiated services)			Traffic shaping/policing			
ACL mapping to priority queue			QoS based on classification			
WRR support			Flow mirror, 802.1p support			
Strict priority support			Priority queue			
QoS based on classification (Based on IP, MAC, VLAN)			SP+WRR			
Rate limiting (Based on per port and per queue)			Flow redirection			
Class-map, Policy-map			DSCP prioritization			
Layer 3						
DHCP relay			ARP Table			
DHCP server			IPv6 ND			
DHCPv6 client			IPv6 Interface			
IP source guard			IPv6 MTU path discovery			
ISATAP			Route-only support			
IPv4Interface			VRRP			

* Dedicated stacking ports can be configured as uplink ports.

MLD snooping (v1, v2)	IGMP Proxy
Route-map	PIM-SM, SSM
Route redistribution	IP source guard
Layer 3 Routing	
Inter-VLAN routing	IPv4 static routing
RIPv2	IPv4 host routing
OSPFv2/v3	IPv6 static routing, IPv6 host routing
IPv6 Unicast routing	IPv4 and IPv6 Dual stack
Policy based routing	Border Gateway Protocol (BGP)
Layer 2	
STP, RSTP, MSTP	Port mirroring (Port, ACL, VLAN Based)
VLAN (MAC, Protocol, Port based)	BPDU filtering
Auto MDI/MDIX	Ping/Trace route/ICMPv6
BPDU guard, Root guard	Storm control (Broadcast, Multicast, Unicast)
IGMP/IGMP snooping v1/v2/v3*	GVRP
LLDP/LLDP MED	Loopback detection
802.1Q VLAN Tagging	802.1x(Guest VLAN)
Private VLAN	Dynamic VLAN
High Availability	
Stacking (Up-to 8 members)	Ring Redundancy Protocol (RRP)
Equal-cost multi path (ECMP)	Ethernet Ring Protection Switching (ERPS)
Storm control (Broadcast, Multicast, Unicast)	Virtual Router Redundancy Protocol (VRRP)
Security	
ACLs	MACsec***
DHCP snooping	Downloadable ACL
802.1x authentication	Dynamic ACL
MAC authentication	Secure copy (SCP)
Radius/Tacacs/Tacacs+	DoS protection
AAA	Local username/password
802.1x authentication (Single Host, Multi Host, Multi session)	Protected ports
SSH	RA guard
Open-Source Support	
SONiC operating system	
Management	
Local GUI	SNMP traps
Industrial standard CLI	Management: RUDDER (Controller)/Standalone
Stacking	Telnet support
SNMP v1/v2c/v3	SNTP
TFTP support	IPv6 management
SPAN/RSPAN	Storage & File management with USB

sFLOW	Firmware auto-install support
RMON (all 4 groups 1,2,3,9)	Password management
Syslog server	
Standard Compliance	
IEEE Standards Compliance	
802.1AB LLDP/ LLDP-MED	802.3ae 10 Gigabit Ethernet
802.1D MAC bridging	802.3at Power over Ethernet Plus
802.1p Mapping to priority queue	802.3u 100Base-TX
802.1s Multiple Spanning Tree (MST)	802.3x flow control
802.1w Rapid Reconfiguration of Spanning Tree (RSTP)	802.3z 1000Base-SX/LX
802.1x Port-based Network Access Control (PNAC)	802.3 MAU MIB (RFC 2239)
802.3 Carrier Sense Multiple Access/Collision Detection (CSMA/CD)	802.1Q VLAN tagging
802.3ab 1000 Base-T	802.3az Energy Efficient Ethernet
802.3 10 Base-T	802.3af Power over Ethernet
802.3ad link aggregation (Dynamic and Static)	
Monitoring and Troubleshooting	
Errdisable detection and recovery	CPU utilization
Device temp/PSU/FAN/status display & alarm	User operation logs
Virtual cable test	Management logs, alarms
ICMPv4/v6	DDM (Digital Diagnostic Monitoring)
Traceroute	UDLD (Unidirectional Link Detection)
Environment	
Operating temperature	-5°C (23°F) to 65°C (149°F)
Humidity	5 % to 95 % RH, non-condensing
Voltage input	100-240V. Frequency: 50/60Hz
Power consumption	≤100W

Physical	QN-CS-4810GF	QN-CS-2410GF	QN-CS-1610GF	QN-CS-241GF
Net Weight	8.90 Kg	8.69 Kg	8.53 Kg	3.86 Kg
Dimensions (H x W x D)	44mm x 440mm x 470mm	44mm x 440mm x 470mm	44mm x 440mm x 470mm	44mm x 440mm X 245mm
Fan	2+1, Hot pluggable	2+1, Hot pluggable	2+1, Hot pluggable	In-built

CERTIFICATION & COMPLIANCES**

Regulatory	FCC
	BIS
	TEC
Environmental	RoHS
	CE

** For more information, visit www.qntmnet.com/certification or email us at sales@qntmnet.com.

ORDERING INFORMATION

Part Number	Description
QN-CS-4810GF	Core Switch, 48×10G SFP+ ports, 6×100G QSFP28 uplink/stacking ports with two hot-swappable power supplies, Includes a cloud controller license and a 3-year online activation warranty
QN-CS-2410GF	Core Switch, 24×10G SFP+ ports, 6×100G QSFP28 uplink/stacking ports with two hot-swappable power supplies, Includes a cloud controller license and a 3-year online activation warranty.
QN-CS-1610GF	Core Switch, 16×10G SFP+ ports, 2×100G QSFP28 uplink/stacking ports with two hot-swappable power supplies, Includes a cloud controller license and a 3-year online activation warranty.
QN-CS-241GF	Core Switch, 16×1G SFP Ports + 8×1G SFP/RJ45 combo ports +4×10G SFPP uplink/stacking ports with two hot-swappable AC+AC power supplies, USB, OOB, Includes a cloud controller license and a 3-year online activation warranty.

SYSTEM UPGRADE INFORMATION***

Part Number	Description
QN-CS-NSU2	System upgrade for networking scale level 2.
QN-CS-SEC-U	System upgrade for enabling MACsec.