

INROOM ACCESS POINT

QN-H-220



Wi-Fi has become an essential amenity as users bring an increasing number of devices into hotel rooms, conference rooms, and classrooms.

PRODUCT OVERVIEW

The Quantum QN-H-220 is meticulously crafted for individual room installations, serving as an 802.11ac Wave 2 Wi-Fi access point. This device boasts a compact, inconspicuous design that prioritizes security and easy mounting.

The QN-H-220 offers a concurrent dual-band solution for 802.11ac Wave 2 wireless networking. With MU-MIMO technology, it delivers impressive speed alongside extensive coverage. Managed by Quantum Rudder.



Up to 1.2 Gbps
Data Rate



MU-MIMO



2x2,
AC Wave2



Dual-Band
Dual-Concurrent



3 Years
Warranty

KEY FEATURES

Loaded with cutting-edge Wave 2 technologies

QN-H-220 encompasses all the latest advancements of an ac wave 2 access point, including channel bonding, MU-MIMO and more.

Exceptional Wi-Fi capabilities

Designed to deliver exceptional Wi-Fi performance, even in medium-density environments with demanding voice and video applications. Enhances coverage, boosts capacity and ensures seamless performance in such settings.

Establish advanced guest Wi-Fi networks for the next-generation

Implement cutting-edge customer service hotspots featuring integrated splash portals and beacons via USB.

Stunning performance

Extends coverage, connects more devices simultaneously with dual MU-MIMO spatial streams and concurrent dual-band 2.4/5GHz radios.

Security against unauthorized use

The access point remains locked for deployment in any other network until decommissioned from the existing network.

Three-year warranty coverage

Benefit from a three-year limited liability manufacturer's warranty starting from the date of device activation.

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac
	2.4 GHz	IEEE 802.11b/g/n
Operating Mode	Access point, Router, Mesh mode	
Networking Mode	IPv4, IPv6, IPv4v6 (Dual stack), Gateway mode(NAT), Bridge mode	
Maximum Data Rates	5 GHz	802.11ac@ 80 MHz:866.7 Mbps
		802.11ac@ 40 MHz:400 Mbps
		802.11ac@ 20 MHz:173.3 Mbps
	2.4 GHz	802.11n@ 40 MHz: 300 Mbps
		802.11a/g@ 20 MHz: 54 Mbps
		802.11b@ 20 MHz: 11 Mbps
Maximum Receiver Sensitivity	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Supported Channels	5 GHz	36-64, 100-144, 149-165 (U-NII-1, U-NII-2A, U-NII-2C , UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
	Dynamic frequency selection (DFS) optimizes the use of available RF spectrum	
Channel Bands	5 GHz	5.15-5.25GHz (U-NII-1), 5.25-5.35GHz (U-NII-2A), 5.47-5.725GHz (U-NII-2C), 5.725-5.85GHz (U-NII-3)
	2.4 GHz	2.4-2.484GHz (ISM)
Modulation Schemes	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11b	BPSK, QPSK, CCK
Radio Chains and Spatial Streams	2x2:2	Streams in 5 GHz- MU-MIMO
	2x2:2	Streams in 2.4 GHz- MU-MIMO
Channel Size	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80 (VHT) MHz
Wireless Security	WPA3-AES personal, enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed-AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	
	WEP-64, WEP-128	
	802.11 w MFP (Management Frame Protection)	
	MAC-based authentication	
	Captive portal-based authentication	
	802.11i	
	Quantum Secure	
	Hide SSID in beacons	

WIPS/WIDS for Various Attack Signatures	Rogue Station Detection
	Deauth attack detection, RTS and CTS abuse attack detection
	Assoc attack detection, Fata jack tool detection, Misconfigured AP detection
	DHCP snooping server detection, Honeypot /Evil Twin attacks detection
	Ad-Hoc connection detection, Password guessing attacks detection
External DB Support	Radius, Active directory, LDAP
Web Authentication	QN-Secure+, RADIUS, Active directory, LDAP
User Authentication	Methods - Captive portal, QN-Secure+, 802.1x (Radius)
	Directory - QIM, Microsoft active directory, LDAP, G suite, Oauth
	Mode - Via Controller /Access points
Roaming	IEEE 802.11k (Assisted Roaming)
	IEEE 802.11v (BSS Transition Management)
	IEEE 802.11r (Fast BSS Transition (FT))
	Pairwise Master Key (PMK) caching
	Opportunistic key caching
	Seamless roaming for captive portal users
Channel / Tx Power Management	Auto / Manual channel selection
	Speedy channel for RF optimization
	Channel switch for RF optimization
	ATP-Automatic Transmit Power management
Client Management	Band steering
	Band balancing
	Airtime fairness
Guest Management	WISPr – Captive portal, HotSpot 2.0
Native Guest Portal	Customized Template
	Authentication Method
	Guest Profile Support
Diagnostics	Ping, Traceroute, Nslookup, Internet speed, Host discovery, Port connectivity, PCAP capture (Wired and Wireless), ARP scanner
Access Control List	Force DHCP
	URL filtering
	Full Client Isolation, Deny inter-user bridging Deny intra-VLAN traffic
	Bandwidth Restriction per SSID/User
	OS restriction
	L2 (MAC) filtering
	L3 (IP) / L4 (Port) filtering
	MAX clients per radio
	Internet freeze per SSID /User
Meshing	Wireless (singlehop / multihop)
	Wired

Radio Management	DTIM interval	
	OFDM Only (Disables 802.11b)	
	BSS Rate and management rate	
	UAPSD (Power save)	
	Inactivity timeout	
Network Management	IEEE 802.11d/h (DFS) support	
	LLDP discovery, SFlow	
	Proxy ARP	
	DHCP options 60 and 82	
	Port forwarding in router mode	
Administration	WLAN scheduling	
	Internet speed test	
	Schedule reboot	
Networking		
Ethernet WAN	WAN (DHCP/Static/PPPoE)	
USB WAN	USB dongle (3G/4G), Mobile tethering (USB)	
Tunneling	GRE, IPSec, Wire guard, OVPN	
Multi-WAN	Yes, Auto-Failover	
DHCP Server	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy	
WAN Security	Ethernet / USB port block management	
PPP Interface	PPPoE	
DNS	Static, Caching	
NAT	Masquerade (SNAT), Port forwarding (DNAT)	
VLAN Support	802.1Q (1 per BSSID or dynamic per user-based on RADIUS), Port-based (Tagged, untagged)	
Quality of Service		
Auto QoS, 802.11e,		
Manual QoS (DSCP based, Voice, Video, BE and BK)		
WMM, 802.1p		
Performance & Capacity		
Peak PHY Rates	5 GHz - 866.7 Mbps	
	2.4 GHz - 300 Mbps	
Client Capacity	Up to 128 clients per access point	
SSID	Up to 16 per access point (8 per Radio)	
RF		
Maximum Aggregate Transmit Power (Adjusted as per country regulations)	5 GHz	24 dBm
	2.4 GHz	26 dBm
Antenna Type	Internal Omni-directional antennas	
Antenna Gain (Max)	5 GHz	3 dBi
	2.4 GHz	3 dBi

EIRP (Adjusted as per country regulations)	5 GHz	27 dBm
	2.4 GHz	29 dBm
Power		
Rating	802.3 af PoE (Class 0) /at PoE+ (Fully functional with all components)	
	12V DC 2A - Fully functional with all components	
Physical Interfaces		
Ethernet	WAN:1 x 10/100/1000 Base-T Ethernet, Auto-MDIX, RJ-45 with 802.3at PoE	
	LAN: 2 x 10/100/1000 Base-T Ethernet, Auto-MDIX, RJ-45	
	PoE Out/LAN: 1 x 10/100/1000 Base-T Ethernet, Auto-MDIX, RJ-45	
	Pass-Thru (Input and Output): 2 x RJ45 based Ethernet	
Buttons	Restart/Reset	
USB	1 x USB 2.0	
LED Indicators	Quick Setup, Cloud / Standalone	
Management		
Device Management	Standalone, Local (web UI), SSH (CLI)	
	Quantum Rudder (Controller based)	
	Quantum Rudder (On-premises VM)	
	Quantum Rudder appliances (RR-200, RR-300, RR400)	
	Through NMS using SNMP MIBs	
	Local device web management	
Device / System Monitoring	SNMP v1, v2c, v3, Syslog	
Controller DR (Disaster Recovery)	Supported	
Device Security		
Certificate	Locally-significant certificates using PKI	
Controller Communication	Encrypted	
Port Access	802.1x RADIUS supplicant	
Application Integration		
PM WANI,		
NMS Integration - ZABBIX, PRTG Monitor, Open NMS		
Environmental		
Operating Temperature	-20°C (-4F) ~ +55°C (+131F)	
Humidity	10% ~ 90% non-condensing	
Standard	Plenum-rated (UL2043)	
Physical		
Dimensions	15cm(L), 8.6cm(W), 2.5cm(H)	
Weight	184g (0.40 lbs)	
Mounting Kit	Suspended ceiling mount, Ceiling mount, Wall mount	

Firmware Management

Cloud-managed firmware update

Scheduled firmware and security update

Firmware upgrade via Access Point local GUI

Certification & Compliances

Regulatory	FCC
	ETA
	BIS
	TEC
Environmental	RoHS
	CE

ORDERING INFORMATION

Part Code	Description
QN-H-220	Quantum Networks QN-H-220 dual-band 802.11ac wave2 in room wireless access point, 2x2:2 streams, 4x1G Base-T Ethernet ports, 2x2 passthru ports, 802.3 af/at PoE support. Includes 3-year limited liability manufacturer's warranty for the access point. Does not include PoE injector or power adaptor. Does not include cloud controller license.