



### PRODUCT OVERVIEW

QN-I-870 is a Wi-Fi 6 Access Point offering high-performance connectivity for any organization experiencing largely growing numbers of IoT and mobility requirements. With a maximum real-world data rate of up to 5.9 Gbps, it delivers high speed, secure, reliable and seamless performance.

QN-I-870 offers a dual-band, dual-concurrent Wi-Fi 6 Access Point that supports 12 Spatial streams (8x8:8 in 5GHz, 4x4:4 in 2.4GHz). OFDMA technology provides highly efficient fast speed, wide coverage and smoother performance. Its ability to manage high-traffic indoor places like auditoriums, stadiums, conference halls and transit hubs makes it an ideal solution for data-demanding streaming Multimedia Applications like 4K video transmissions while assisting latency-sensitive voice and data applications with firm Quality-of-Service.

Easily deploy futuristic customer engagement solutions using BLE Beacon powered by a USB port.

QN-I-870 is managed by Quantum Rudder. Easily deploy futuristic customer engagement solutions using BLE Beacon powered by a USB port.

### KEY FEATURES

- **Packed with the latest 802.11ax technology.**  
QN-I-870 is packed with all the advances of High-Efficiency supported 11ax Access Point. It supports Wi-Fi 6 features such as OFDMA, Target Wake Time, BSS Colouring, and Spatial Reuse.
- **Phenomenal Wi-Fi performance.**  
Engineered for phenomenal Wi-Fi performance even in high-density environments for demanding voice and video applications. Provides improved coverage, increased capacity, and seamless performance in dense environments.
- **Build next-generation guest Wi-Fi networks.**  
Deploy next-generation customer service hotspots with integrated splash portal and BLE Beacons.
- **Theft prevention functionality.**  
Access Point is locked for deployment in any other network until decommissioned from the existing network.
- **Three-years warranty.**  
Three-year limited liability manufacturer's warranty from the date of activation of the device.



Up to 5.9 Gbps  
Data Rate



5G  
Connectivity



2.4 GHz - 4x4,  
5 GHz - 8x8



MU MIMO  
With OFDMA



3 Years  
Warranty

Wi-Fi		
Wi-Fi Standards	5 GHz	IEEE 802.11a/n/ac/ax
	2.4 GHz	IEEE 802.11b/g/n/ax
Operating Mode	Access point, Router, Mesh mode	
Networking Mode	IPv4, IPv6, IPv4v6 (Dual stack), Gateway mode(NAT), Bridge mode	
Maximum Data Rates	5 GHz	802.11ax@ 160 MHz: 4804 Mbps
		802.11ax@ 80 MHz: 4804 Mbps
		802.11ax@ 40 MHz: 2294.1 Mbps
		802.11ax@ 20 MHz: 1147.1 Mbps
		802.11ac@ 80 MHz: 3466.7 Mbps
		802.11ac@ 40 MHz: 1600 Mbps
	2.4 GHz	802.11ac@ 20 MHz: 693.3 Mbps
		802.11ax@ 40 MHz: 1147.1 Mbps
		802.11ax@ 20 MHz: 573.5 Mbps
		802.11n@ 40 MHz: 917.6 Mbps
Maximum Receiver Sensitivity	5 GHz	-98 dBm
	2.4 GHz	-93 dBm
Supported Channels	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII-3 compliant) (As per country regulations)
	2.4 GHz	1-13 (As per country regulations)
		Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
Modulation Schemes	802.11ax	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
	802.11ac	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
	802.11a/g/n	BPSK, QPSK, 16-QAM, 64-QAM
	802.11b	BPSK, QPSK, CCK
Spatial Streams	8x8:8	Streams in 5GHz-OFDMA with MU-MIMO
	4x4:4	Streams in 2.4GHz- OFDMA with MU-MIMO
Channel Size	802.11n	20/40 (HT) MHz
	802.11ac	20/40/80 (VHT) MHz
	802.11ax	20/40/80/160 (HE) MHz
Wireless Security	WPA3-AES personal, Enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed- AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	
	WEP-64, WEP-128	
	802.11 w MFP (Management Frame Protection)	
MAC based authentication		

Wireless Security	Captive portal-based authentication	
	802.11i	
	Quantum SECURE	
	Hide SSID in beacons	
WIPS/WIDS for Various Attack Signatures	Rogue Station Detection	
	Deauth attack Detection, RTS and CTS Abuse attack Detection	
	Assoc attack Detection, Fata jack tool Detection,	
	DHCP snooping server Detection, Honeypot / Evil Twin attacks Detection	
	Dos attack Detection, DDos attack Detection, Misconfigured AP Detection	
	SSH Bruteforce attacks Detection, Man in the Middle attacks Detection	
	Port Scanning Detection, AdHoc Connection Detection, Password Guessing attacks Detection	
External DB Support	Radius, Active directory, LDAP	
Web Authentication	QN-Secure+, RADIUS, Active directory, LDAP	
User Authentication	Methods	Captive portal, QN-Secure+, 802.1x (Radius)
	Directory	QIM, Microsoft active directory, LDAP, Gsuite, Oauth
	Mode	Via Controller /Access points
Roaming	IEEE 802.11k (Assisted Roaming)	
	IEEE 802.11v (BSS Transition Management)	
	IEEE 802.11r (Fast BSS Transition (FT))	
	Pairwise Master Key (PMK) caching	
	Opportunistic key caching	
	Seamless roaming for captive portal users	
Channel / Tx Power Management	Auto / Manual channel selection	
	Speedy channel for performance optimization	
	Channel switch for performance optimization	
	ATP-Automatic Transmit Power management	
Client Management	Band steering	
	Band balancing	
	Airtime fairness	
Guest Management	WISPr – Captive portal, HotSpot 2.0	
Native Guest Portal	Customized Template	Yes (User define, Theme based)
	Authentication Method	Click-through, Access code, Self-sign-up (SMS, Email), Sponsor based (Domain-based, Individual Email ID based)
	Guest Profile Support	Pass validity, Bandwidth restriction, Quota based

Diagnostics	Ping, Traceroute, Nslookup, Internet Speed, Host Discovery, Port Connectivity, PCAP capture (Wired and Wireless), ARP Scanner
Access Control List	Force DHCP
	URL & Application filtering
	Full Client Isolation, Deny inter user bridging, Deny intra VLAN traffic
	Bandwidth Restriction per SSID/per User
	OS restriction
	L2 (MAC) filtering
	L3 (IP) / L4 (Port) filtering
	MAX clients per radio
Meshing	Wireless (singlehop / multihop)
	Wired
Radio Management	DTIM interval
	OFDM Only (Disables 802.11b)
	BSS Rate and management rate
	UAPSD (Power save)
Network Management	Inactivity timeout
	IEEE 802.11d/h (DFS) support
	LLDP discovery, SFlow
	Proxy ARP
	DHCP options 60 and 82
Administration	Port forwarding in router mode
	WLAN scheduling
	Internet speed test
Wi-Fi6 Features	Schedule reboot
	Target wake time
	BSS colouring
	Spatial reuse
	Orthogonal frequency division multiple access (OFDMA)
Advance Features	Preamble puncturing
	Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
	Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas
	Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz
Space-time block	
<b>Networking</b>	
Ethernet WAN	WAN (DHCP/Static/PPPoE)
USB WAN	USB dongle (3G/4G), Mobile tethering (USB)
Protocols	Static, RIP v2, OSPF v2
Tunneling	GRE, IPSec, Wire guard, OVPN

Multi WAN	Yes, Auto Failover	
DHCP Server	4 Scope, DHCP lease, DHCP MAC reservation, DNS proxy	
WAN Security	Ethernet / USB port block management	
PPP Interface	PPPoE, L2TP, L2TP with IPSec	
DNS	Static, Caching, Dynamic DNS	
NAT	Masquerade (SNAT), Port forwarding (DNAT)	
VLAN Support	802.1Q (1 per BSSID), Port-based (Tagged, untagged),	
IoT	Supported (With BLE)	
<b>Quality of Service</b>		
Auto QoS, 802.11e,		
Manual QoS (DSCP based, Voice, Video, BE and BK)		
WMM		
802.1p		
<b>Performance &amp; Capacity</b>		
Peak PHY Rates	5 GHz	4804 Mbps (802.11ax)
	2.4 GHz	1147 Mbps (802.11ax)
Client Capacity	Up to 1024 clients per Access point	
SSID	Up to 32 per access point (16 per Radio)	
<b>RF</b>		
Maximum Aggregate Transmit Power (Adjusted as per country regulations)	5 GHz	24 dBm
	2.4 GHz	27 dBm
Antenna Type	Built-in integrated antenna for both radios and BLE	
Antenna Gain (Max)	5 GHz	4 dBi
	2.4 GHz	4 dBi
EIRP (Adjusted as per country regulations)	5 GHz	28 dBm
	2.4 GHz	31 dBm
Radio Interfaces	Sensor radio optional	
<b>Power</b>		
Rating	802.3 at / bt (PoE++)- Fully functional with all components	
	12V DC 3A - Fully functional with all components	
<b>Physical Interfaces</b>		
Ethernet	WAN: 1 x 5 G Base-T ethernet, Auto MDIX, RJ-45 with 802.3at PoE	
	LAN: 1 x 1 G Base-T ethernet, Auto MDIX, RJ-45	
USB	1 x USB 3.0 port	
Buttons	Restart/Reset	
LED Indicators	2.4 GHz, 5 GHz, Power, Uplink	

<b>Management</b>	
Device Management	Standalone, Local (web UI), SSH (CLI)
	Quantum Rudder (Controller based)
	Quantum Rudder (On-premises VM)
	Quantum Rudder appliances (RR-200, RR-300, RR400)
	Through NMS using SNMP MIBs
	Local device web management
Device /System Monitoring	SNMP v1, v2c, v3, Syslog
Controller DR (Disaster Recovery)	Supported
<b>Device Security</b>	
Certificate	Locally-significant certificates using PKI
Controller Communication	Encrypted
Switch Port Access	802.1x RADIUS supplicant
<b>Application Integration</b>	
PM WANI,	
NMS Integration - ZABBIX, PRTG Monitor, Open NMS	
<b>Environmental</b>	
Operating Temperature	0°C (32°F) to 50°C (122°F)
Humidity	Up to 95%, non-condensing
Standard	Plenum-rated (UL2043)
<b>Physical</b>	
Dimensions	19.5 cm (L) x 20.1 cm (W) x 3.98 cm (H)
Weight	0.7 kg (1.54 lbs)
Mounting kit	Ceiling mount, Wall mount
<b>Firmware Management</b>	
Cloud manage Firmware Update	
Scheduled Firmware Update	
Security Update	
<b>Certifications</b>	
Regulatory	FCC
Standard	IEC-60950
Environmental	CE
	RoHS